

Fast and powerful strobe ideal for compact digital or SLR photography featuring DS-TTL and LED target light.



YS-110α

Product No 03111

SPECIAL OFFER

Specifications

[Guide Number (ISO 100/m) (land)] 22 [Beam Angle] 105° x 105° (with diffuser) [Batteries] 4xAA ■A: 6V
■Ni-MH: 4.8V [Number of Flashes] ■A: 230 ■Ni-MH: 330 [Recycle time (full)] ■A: 2.5 sec. ■Ni-MH: 1.9 sec.
[Color temperature] 5400K [Color temperature w/diffuser] 5100K [Depth rating] 60m / 200ft [Dimensions (WxHxD)]
88x115x150mm / 3.5x4.6x6inch [Weight] 700g / 24.5oz [Underwater weight] -10g / -0.4oz

[Others]

- Exposure control: DS-TTL, TTL, Light level control dial (GN): 1.4 / 2 / 2.5 / 2.8 / 3.5 / 4 / 4.5 / 5.6 / 6.7 / 8 / 11 / 16 / 22 (13 steps)
- Pre-flash control: Equipped with pre-flash cancel mode ○DS-TTL function ○Auto power OFF function
- Sync cord: 5-pin Sync cord/N17100, Fiber-Optic Cable (L-type) ○Over-pressure relief valve ○LED target light

*When the YS-110 α strobe is used with a compact digital camera in a housing, use the Fiber-Optic Cable (L-type).
*Specifications, external design of product and product features may change without notice to improve product.

SEA&SEA
THE UNDERWATER IMAGING COMPANY