



U/W Strobe

YS-01

(Product No.03112)

Affordable compact DS-TTL and manual strobe with target light.

- ▶ Circular beam angle of 100 x 100 degrees.
- ▶ Maximum guide number is 20 (m).
- ▶ Can be switched between DS-TTL and (ten-level) manual control modes, enabling fine adjustment of the light power output according to the photographer's requirements.
- ▶ Powered by 4x AA batteries, for the optimum number of flashes.
- ▶ Quick recycle time of 1.9 sec. (with 2700mAh nickel-metal hydride batteries).
- ▶ Equipped with a high-luminance white LED target light (1w) which also indicates the optical axis of the strobe.

Product Specifications

Guide Number (ISO 100/m) (land)	20	Weight	450g / 15.8oz (w/o batteries) * Attached a fixing bolt to the Strobe.
Beam Angle	100°x 100° (with diffuser 110°x110°)	Underwater weight	-10g / -0.4oz(w/ batteries)
Batteries	■4xAA ●A: 6V ●Ni-MH: 4.8V	Others	<input type="checkbox"/> Exposure control: DS-TTL, Light level control dial (GN): 1 / 1.4 / 2 / 2.8 / 4 / 5.6 / 8 / 11 / 16 / 20 (10 steps)
Number of Flashes	●A:230 ●Ni-MH:330	<input type="checkbox"/> Pre-flash control: Equipped with pre-flash cancel mode	
Recycle time (full)	●A:2.5 sec. ●Ni-MH:1.9 sec.	<input type="checkbox"/> DS-TTL function <input type="checkbox"/> Slave function	
Color temperature	5600K	<input type="checkbox"/> Auto power OFF function <input type="checkbox"/> Sync cord: Fiber-Optic Cable	
Color temperature w/diffuser	5250K	<input type="checkbox"/> Over-pressure relief valve <input type="checkbox"/> LED target light	
Depth rating	75m / 250ft		
Dimensions (WxHxD)	68x108x129mm / 2.7x4.3x5.2inch		

*A: Alkaline, Ni-MH: Nickel-Metal-Hydride

For compatible cameras, please refer to "Compatibility List" for the strobe and digital cameras on the SEA&SEA website.
→<http://www.seaandsea.jp/products/strobe/compatibilitychart/a.html>