

Ultra-compact strobe ideal for wide-angle and macro photography featuring DS-TTL and LED target light.



YS-01 **New**

Product No 03112

SPECIAL OFFER

Specifications

[Guide Number (ISO 100/m) (land)] 20 [Beam Angle] 100° x 100° (with diffuser) 110° x 110° [Batteries] 4xAA ■ A: 6V ■ Ni-MH: 4.8V [Number of Flashes] ■ A: 230 ■ Ni-MH: 330 [Recycle time (full)] ■ A: 2.5 sec. ■ Ni-MH: 1.9 sec. [Color temperature] 5600K [Color temperature w/diffuser] 5250K [Depth rating] 75m / 250ft [Dimensions (WxHxD)] 68x108x129mm / 2.7x4.3x5.2inch [Weight] 505g / 17.7oz [Underwater weight] -10g / -0.4oz

[Others]

- Exposure control: DS-TTL, TTL, Light level control dial (GN): 1.4 / 2 / 2.5 / 2.8 / 3.5 / 4 / 4.5 / 5.6 / 6.7 / 8 / 11 / 16 / 22 (13 steps)
- Pre-flash control: Equipped with pre-flash cancel mode ○ DS-TTL function ○ Auto power OFF function
- Sync cord: 5-pin Sync cord/N17100, Fiber-Optic Cable (L-type) ○ Over-pressure relief valve ○ LED target light

*Use a fiber-optic cable to connect the strobe to a digital camera in a housing

*Specifications, external design of product and product features may change without notice to improve product.

SEA&SEA
THE UNDERWATER IMAGING COMPANY