



U/W Strobe

YS-02

(Product No.03113)

Economic compact manual strobe.

- ▶ Circular beam angle of 100 x 100 degrees.
- ▶ Maximum guide number is 20 (m).
- ▶ Equipped with a ten-level manual control function.
- ▶ Powered by 4x AA batteries, for the optimum number of flashes.
- ▶ Quick recycle time of 1.9 sec. with nickel-metal hydride batteries (2700mAh).

Product Specifications

Guide Number (ISO 100/m) (land)	20	Others	
Beam Angle	100°x 100° (with diffuser 110°x110°)	<input type="checkbox"/> Exposure control: DS-TTL, Light level control dial (GN):	1 / 1.4 / 2 / 2.8 / 4 / 5.6 / 8 / 11 / 16 / 20 (10 steps)
Batteries	■4xAA ●A: 6V ●Ni-MH: 4.8V	<input type="checkbox"/> Pre-flash control: Equipped with pre-flash cancel mode	
Number of Flashes	●A: 230 ●Ni-MH: 330	<input type="checkbox"/> Slave function	
Recycle time (full)	●A: 2.5 sec. ●Ni-MH: 1.9 sec.	<input type="checkbox"/> Auto power OFF function	
Color temperature	5600K	<input type="checkbox"/> Sync cord: Fiber-Optic Cable	
Color temperature w/diffuser	5250K	<input type="checkbox"/> Over-pressure relief valve	
Depth rating	75m / 250ft		
Dimensions (WxHxD)	68x108x129mm / 2.7x4.3x5.2inch		
Weight	445g / 15.6oz (w/o batteries)		
	* Attached a fixing bolt to the Strobe.		
Underwater weight	-10g / -0.4oz(w/ batteries)		

*A: Alkaline, Ni-MH: Nickel-Metal-Hydride

For compatible cameras, please refer to "Compatibility List" for the strobe and digital cameras on the SEA&SEA website.
→<http://www.seaandsea.jp/products/strobe/compatibilitychart/b.html>