

The complete underwater strobe which realizes power, speed and quality

- Excellent night-time visibility. The illuminated control panel is ideal for night diving
- ► Maximum guide number is a powerful 32 (ISO 100, meter). Recycle time is only 1.5 sec
- ▶DS-TTL II automatic exposure control with improved accuracy and stability
- ► EV control function can finely tune the amount of light emitted
- The target light can be adjusted in 2 steps









- Two diffusers and red filters included with the strobe as standard
- ▶ Custom mode is a new innovation which allows the YS-D2 to be compatible with cameras with non-standard pre-flash settings

Product Specifications	
Guide Number (ISO 100/m) (land)	32, 24 (with Diffuser 100 attached), 20 (with Diffuser 120 attached)
Beam Angle	80° x 80° (without Diffuser), 100° x 100°(Diffuser 100), 120° x 120° (Diffuser 120)
Recycle time (full)	A: 3.0 sec. Ni-MH: 1.5 sec
Depth rating	100m / 330ft
Dimensions (WxHxD)	(Excluding protruding part(s) and the arm holder.) 89 x 133 x 116mm / 3.5 x 5.2 x 4.6 inches
	(incl. YS base but excluding protruding parts)
Weight	623g / 22.0oz (w/o batteries) (inc. YS-mount and fixing bolt. Without batteries)
Underwater weight	Approx.+40g / 1.4oz (incl. batteries)
Others Exposure control: DS-TTL II, Slave TTL, Light level control dial (GN): 1 / 1.4 / 2 / 2.8 /4 / 5.6 /8 / 11 / 16 / 22 / 32 (11 steps) Sync cord: 5-pin Sync cord/N, Fiber-Optic Cable	