MDX housing for Nikon D7000, supports fiber-optic cable connection.





Optional Sync Cord Connector N is employed.

Conventional Sync Cord N can be used by removing the connector cap and then fixing the Optional Sync Cord Connector N on the housing. The Strobe Connector N can be easily fixed by consumers. Even when the connector gets wet, the connector can be replaced on the spot.



With both hands on the grips, movie shooting can be activated with a small movement of your finger tip.

Though the housing boasts depth rating of 100mm/330ft, buttons on the housing can be effortlessly depressed. As necessary controls for movie shooting can be manipulated with levers, subtle control is possible. The positions of the grips have been revised for better access to various controls.



Compatible with the VF45 1.2x

By attaching the VF45 1.2x prism viewfinder (magnification ratio of 1.2x) to the housing, the magnification increases to 1.2x and entire field of view can be seen at the same time. Recommended for users committed to strict composition and focusing.



Compact design to the limit.

Two Fiber-optic cable sockets

Every detail of the housing is precision machined from a solid aluminum block. The housing is protected by highly corrosion and abrasion resistant anodizing coating.

Accessories

VF45 1.2x

Product No. 46111

A 45° prism viewfinder. Covering the entire field of view, the VF45 enhances magnification by 1.2x and enables subtle framing and focusing of subjects. The eyepiece rotates 360° in increments of 90° to provide the ideal camera position in either landscape or portrait.



Fiber-Optic Cable (L-type)

Product No. 50107

This fiber-optic cable resists bending and has improved light-conducting efficiency.



5-pin Sync Cord/N

Product No. 17100

