A compact and full-featured waterproof compact digital camera set. 12.2 effective megapixels and 4x optical zoom.





Construction	Polycarbonate
Depth rating	55m / 180ft
Dimensions (WxHxD)	140x109x82.5mm / 5.6x4.4x3.3inch
Weight	Approx. 385g / 13.5oz (excluding hand strap)
Underwater weight	Approx. 30g / 1.05oz
Compatible strobes	YS-01, YS-02, YS-250PRO

*The YS-110 α can be made to be compatible through a firmware update. For details, please inquire at a representative sales office.



□Power button

□Wide-angle / Thumbnail display button

□Telephoto / Enlarged view button

☐Mode selection button

■ A / DISP. button

□ ► / Flash / Macro button

☐Function / OK button

☐MENU button

□Playback button

☐ ✓ / Face Detection button

DX-GE5

DX-GE5 Camera and Housing Set

DX-GE5 Camera and Housing Set (Smoky gray) Product No. 06633

A waterproof camera, so no need to worry even if it gets wet

The DX-GE5 camera is waterproof to 5m / 16ft without it's housing, making it versatile for all outdoor sports activities from water to snow. The DX-GE5 housing is rugged dependable allowing full functionality of the camera to 55m / 180ft.



Compatible with Wide-Angle **Conversion Lens**

The optional Wide-Angle Conversion Lens for DX-860G can be attached/removed even underwater.

Use of the wide-angle conversion lens allows images to be taken at an even wider angle.

*Slight vignetting (dimming) may occur in the four corners of the image. Slightly zoom in to telephoto to eliminate vignetting. With the wide-angle conversion lens for DX-860G



Light and compact for better portability

The DX-GE5 housings was redesigned and improved for better ergonomics offering access to all controls and maximum convenience while underwater.



High definition CCD - 1/2.3-inch primary color CCD with 12.20 effective megapixels and 4x optical zoom lens (38 to 152mm).

Equipped with underwater photo and video modes ideal for capturing perfect underwater images or video.

The camera is waterproof to 5m / 16ft. (*Determined based on General Imaging Company testing methods.)

2.7-inch LCD monitor (with an automatic brightness adjustment function). Approx. 230,000-dot LCD monitor that's easy to see when checking photos while shooting or during playback.

When you turn the retractable cable socket, the fiber-optic cable socket slides and is aligned with position of the built-in flash and fixed.

Compatible with highly sensitive ISO 1600 photography.

The housing rear caseback can be opened/closed while the housing is mounted on a camera tray.

Accessories

Wide-Angle Conversion Lens for DX-860G Product No. 52115

This wide-angle conversion lens covers a maximum field angle equivalent to approx. 28mm (35mm film camera equivalent) when used with the DX-GE5 underwater.

